

Annexure -I
CISCO SFP Small form-factor pluggable transceiver
CISCOR
(Cisco GLC-SX-MMD=)

Specification

Type of Transceiver	SFP
On Site OEM Warranty (Year)	5
Type of Transceiver	SFP
SFP Mode	Multi
Supported Protocols	1000BASE-SX
Compatability with OEMs Products	CISCO
Wavelength(nm)	850
Fibre Cable Type	OM4
Core Size (Micron)	50
Maximum Data Rate	1000
Modal Bandwidth (MHz/Km)	0
Max.Cable Distance	550
Optical Component (nm)	850
Digital Optical Monitoring (DOM) Support	Yes
Interface	Not Applicable
Tx Power (dBm)	-9.5
Receiver Sensitivity (dBm)	-17
Operating Temperature Range(Degree C)	0 to 70
Operating Humidity (RH) (%)	NA

[Handwritten signature]

[Handwritten signature]

[Handwritten signature]

[Handwritten signature]

[Handwritten signature]

CISCO SFP Small form-factor pluggable transceiver
CISCOR
(GLC-LH-SMD= -5Y)

Type of Transceiver	SFP
On Site OEM Warranty (Year)	5
Type of Transceiver	SFP
SFP Mode	Single
Supported Protocols	1000BASE-LH
Compatability with OEMs Products	CISCO
Wavelength(nm)	1310
Fibre Cable Type	SINGLE MODE
Core Size (Micron)	0
Maximum Data Rate	1000
Modal Bandwidth (MHz/Km)	0
Max.Cable Distance	10
Optical Component (nm)	0
Digital Optical Monitoring (DOM) Support	Yes
Interface	LC
Tx Power (dBm)	-9.5
Receiver Sensitivity (dBm)	-20
Operating Temperature Range(Degree C)	0 to 70
Operating Humidity (RH) (%)	NA

Li

Waf

Shu

Ant

VJ

K

Quene